AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1	1. (Currently amended) A method for logging file system operations,
2	comprising:
3	receiving a request to perform a file system operation;
4	making a call to an underlying file system to perform the file system
5	operation; and
6	logging the file system operation to a log within a log device to facilitate
7	recovery of the file system operation in the event of a system failure before the file
8	system operation is committed to non-volatile storage;
9	wherein the request to perform the file system operation is received at a
0	primary server in a highly available system; and
1	wherein the log device is located on a secondary server that is separate
2	from the primary server in the highly available system and that acts as a backup
3	for the primary server: and
4	wherein locating the log on the secondary server facilitates failover to the
5	secondary server when the primary server fails.
ı	
1	2. (Original) The method of claim 1, wherein logging the file system
2	operation involves storing an identifier for the file system operation to the log
3	device.

1	3. (Original) The method of claim 1, further comprising periodically
2	committing the log to the underlying file system by:
3	freezing ongoing activity on a file system;
4	making a call to the underlying file system to flush memory buffers to non-
5	volatile storage, whereby outstanding file system operations are guaranteed to be
6	committed to non-volatile storage;
7	removing outstanding file system operations from the log; and
8	unfreezing the ongoing activity on the file system.
1	4. (Original) The method of claim 1, wherein upon a subsequent computer
2	system startup, the method further comprises:
3	examining the log within the log device;
4	replaying any file system operations from the log that have not been
5	committed to non-volatile storage.
1	5. (Original) The method of claim 1, further comprising checking for
2	dependencies between the file system operation and ongoing file system
3	operations; and
4	if dependencies are detected, ensuring that the file system operation and
5	the ongoing file system operations complete in an order that satisfies the
6	dependencies.
1	6 (Canceled).
1	7. (Original) The method of claim 1, further comprising:
2	associating the file system operation with a transaction identifier for a set
3	of related file system operations; and

4	wherein logging the file system operation involves storing the file system
5	operation with the transaction identifier to the log device.
1	8. (Original) The method of claim 1, wherein logging the file system
2	operation involves:
3	determining if the file system operation belongs to a subset of file system
4	operations that are subject to logging; and
5	if so, logging the file system operation.
1	9. (Original) The method of claim 8, wherein the subset of file system
2	operations are non-idempotent file system operations.
1	10. (Original) The method of claim 1, wherein the log device stores the
2	file system operation in volatile storage.
1	11. (Original) The method of claim 1, wherein the log device stores the
2	file system operation in non-volatile storage.
1	12. (Currently amended) A computer-readable storage medium storing
2	instructions that when executed by a computer cause the computer to perform a
3	method for logging file system operations, the method comprising:
4	receiving a request to perform a file system operation;
5	making a call to an underlying file system to perform the file system
6	operation; and
7	logging the file system operation to a log within a log device to facilitate
8	recovery of the file system operation in the event of a system failure before the file
9	system operation is committed to non-volatile storage;

10	wherein the request to perform the file system operation is received at a
11	primary server in a highly available system; and
12	wherein the log device is located on a secondary server that is separate
13	from the primary server in the highly available system and that acts as a backup
14	for the primary server; and
15	wherein locating the log on the secondary server facilitates failover to the
16	secondary server when the primary server fails.
1	13. (Original) The computer-readable storage medium of claim 12,
2	wherein logging the file system operation involves storing an identifier for the file
3	system operation to the log device.
1	14. (Original) The computer-readable storage medium of claim 12,
2	wherein the method further comprises periodically committing the log to the
3	underlying file system by:
4	freezing ongoing activity on a file system;
5	making a call to the underlying file system to flush memory buffers to non-
6	volatile storage, whereby outstanding file system operations are guaranteed to be
7	committed to non-volatile storage;
8	removing outstanding file system operations from the log; and
9	unfreezing the ongoing activity on the file system.
1	15. (Original) The computer-readable storage medium of claim 12,
2	wherein upon a subsequent computer system startup, the method further
3	comprises:
4	examining the log within the log device;
5	replaying any file system operations from the log that have not been
6	committed to non-volatile storage.

1	16. (Original) The computer-readable storage medium of claim 12,
2	wherein the method further comprises checking for dependencies between the file
3	system operation and ongoing file system operations; and
4	if dependencies are detected, ensuring that the file system operation and
5	the ongoing file system operations complete in an order that satisfies the
6	dependencies.
1	17 (Canceled).
1	18. (Original) The computer-readable storage medium of claim 12,
2	wherein the method further comprises:
3	associating the file system operation with a transaction identifier for a set
4	of related file system operations; and
5	wherein logging the file system operation involves storing the file system
6	operation with the transaction identifier to the log device.
1	19. (Original) The computer-readable storage medium of claim 12,
2	wherein logging the file system operation involves:
3	determining if the file system operation belongs to a subset of file system
4	operations that are subject to logging; and
5	if so, logging the file system operation.
1	20. (Original) The computer-readable storage medium of claim 19,
2	wherein the subset of file system operations are non-idempotent file system
3	operations.
1	21. (Original) The computer-readable storage medium of claim 12,
2	wherein the log device stores the file system operation in volatile storage.

	22. (Original) The computer-readable storage medium of claim 12,
2	wherein the log device stores the file system operation in non-volatile storage.
	23. (Currently amended) An apparatus that logs file system operations,
2	comprising:
}	a receiving mechanism that is configured to receive a request to perform a
1	file system operation;
5	a calling mechanism that is configured to make a call to an underlying file
5	system to perform the file system operation; and
7	a logging mechanism that is configured to log the file system operation to
3	a log within a log device to facilitate recovery of the file system operation in the
)	event of a system failure before the file system operation is committed to non-
)	volatile storage;
1	wherein the receiving mechanism is located within a primary server in a
2	highly available system; and
3	wherein the log device is located within a secondary server that is separat
4	from the primary server in the highly available system and acts as a backup for the
5	primary server: and
6	wherein locating the log on the secondary server facilitates failover to the
7	secondary server when the primary server fails.
1	24. (Original) The apparatus of claim 23, wherein the logging mechanism
2	is configured to store an identifier for the file system operation to the log device.
1	25. (Original) The apparatus of claim 23, wherein the logging mechanism
2	is configured to periodically:
3	freeze ongoing activity on a file system:

4	make a call to the underlying file system to flush memory buffers to non-
5	volatile storage, whereby outstanding file system operations are guaranteed to be
6	committed to non-volatile storage;
7	remove outstanding file system operations from the log; and to
8	unfreeze the ongoing activity on the file system.
1	26. (Original) The apparatus of claim 23, further comprising a recovery
2	mechanism that operates during system startup, wherein the recovery mechanism
3	is configured to:
4	examine the log within the log device; and to
5	replay any file system operations from the log that have not been
6	committed to non-volatile storage.
1	27. (Original) The apparatus of claim 23, further comprising a dependency
2	handler that is configured to:
3	check for dependencies between the file system operation and ongoing file
4	system operations; and to
5	ensure that the file system operation and the ongoing file system
6	operations complete in an order that satisfies dependencies if dependencies are
7	detected.
1	28 (Canceled).
1	29. (Original) The apparatus of claim 23, further comprising a transaction
2	mechanism that is configured to associate the file system operation with a
3	transaction identifier for a set of related file system operations; and
4	wherein the logging mechanism is configured to log the file system
5	operation with the transaction identifier to the log device.

- 30. (Original) The apparatus of claim 23, wherein the logging mechanism is configured to: determine if the file system operation belongs to a subset of file system 3 operations that are subject to logging; and to 4 log the file system operation if the file system operation belongs to the 5 subset of file system operations that are subject to logging.
- 31. (Original) The apparatus of claim 30, wherein the subset of file system operations are non-idempotent file system operations.
- 32. (Original) The apparatus of claim 23, wherein the log device is configured to store the file system operation in volatile storage. 2

6

33. (Original) The apparatus of claim 23, wherein the log device is configured to store the file system operation in non-volatile storage. 2